


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : H04L 27/38		A1	(11) International Publication Number: WO 98/35477
			(43) International Publication Date: 13 August 1998 (13.08.98)
(21) International Application Number: PCT/GB98/00355		(81) Designated States: GB, JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 5 February 1998 (05.02.98)			
(30) Priority Data: 9702304.8 5 February 1997 (05.02.97) GB 9709713.3 13 May 1997 (13.05.97) GB		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(71) Applicant (for all designated States except US): SYMBIONICS LTD. (GB/GB); St. John's Innovation Park, Cowley Road, Cambridge CB4 4WS (GB).			
(72) Inventor; and (75) Inventor/Applicant (for US only): RUDKIN, Paul (GB/GB); 5 The Elms, Haslingfield, Cambridge CB3 7ND (GB).			
(74) Agents: BUTCHER, Ian, James et al.; A.A. Thornton & Co., Northumberland House, 303-306 High Holborn, London WC1V 7LE (GB).			

(54) Title: DEMODULATION WITH SEPARATE BRANCHES FOR PHASE AND AMPLITUDE



## (57) Abstract

A receiver architecture is disclosed for use in Time-Division Multiple Access (TDMA) and related digital radio applications which combines the principal benefits of the conventional hard-limiting and linear receiver architectures to support switched-antenna diversity and multipath equalisation without the need for receiver gain control. A further feature of the receiver architecture is that minimises the dynamic range needed by the digital signal processing stages thereby reducing complexity, power consumption and cost compared to known arrangements. The (TDMA) radio frequency signal is separated into two components by the analogue section of the receiver: one component characterising the signal's phase, either absolute or differential, the second component characterising the signal's instantaneous magnitude. The (constant-envelope) phase component is digitised by an analogue-to-digital converter (ADC) to form a sequence of phase samples. In a parallel path, the magnitude component is digitised by a second, synchronised ADC, digitally processed to obtain a sequence of coefficients characterising the normalised envelope variations and this is then combined with corresponding (in time) samples of the phase sequence to form a single, composite sequence characterising both the phase and amplitude variations of the received radio frequency signal. This composite sequence is then processed by a digital demodulator/equaliser to recover the transmitted data.

18567